

Air Suspended Optical Tables



Specifications:

- ☞ Surface flatness: $60 \times 60 \text{ cm}^2 \pm 0.1 \text{ mm}$
- ☞ Protection for electricity interruption & air rupture
- ☞ Holes distance: M6 tapping with a distance 25mm from edge.
- ☞ Rigid magnetic steel plate desktop, inner with honey comb steel structure.
- ☞ **Patented air suspension isolator**
- ☞ **Patented auto leveling system**
- ☞ 4" PU caster for easy moving.
- ☞ Cylinder or square type united leg

| Model | Width mm | Depth mm | Hight mm | Thickness mm |
|------------|----------|----------|----------|--------------|
| TU-60×60 | 600 | 600 | 800 | 100 |
| TU-60×90 | 600 | 900 | 800 | 100 |
| TU-90×90 | 900 | 900 | 800 | 100 |
| TU-90×120 | 900 | 1200 | 800 | 100 |
| TU-90×150 | 900 | 1500 | 800 | 100 |
| TU-90×180 | 900 | 1800 | 800 | 100 |
| TU-100×100 | 1000 | 1000 | 800 | 100 |
| TU-100×150 | 1000 | 1500 | 800 | 100 |
| TU-100×180 | 1000 | 1800 | 800 | 100 |
| TU-100×200 | 1000 | 2000 | 800 | 100 |
| TU-120×120 | 1200 | 1200 | 800 | 100 |
| TU-120×150 | 1200 | 1500 | 800 | 100 |
| TU-120×180 | 1200 | 1800 | 800 | 100 |
| TU-120×240 | 1200 | 2400 | 800 | 100 |
| TU-120×300 | 1200 | 3000 | 800 | 100 |



Vibration Isolation Sensor