

Portable Microprocessor Dewpoint meter

TouchDew TD-301P



Features:

- ◎ 4.3" Touch Panel Control System
- ◎ Operation Easily, Large Words
- ◎ Dew Point/ ppm(v) Switchable
- ◎ Realtime Trend Chart
- ◎ Compact Design and Weight Balance
- ◎ Built in Rechargeable Battery for 12 Hours
- ◎ Wide Measuring Range
- ◎ NPL Traceable Calibration
- ◎ Readable CSV Format Data by USB Disk

Specifications :

Model	: TD-301P
Measuring range	: +20/-100 °C or 0-3000 ppm(v)
Accuracy	: ± 2 °C
Display	: 4.3" Touch screen
Display unit	: °C/ °F Dewpoint, ppm(v)
Resolution	: 0.1 °C / 0.01 °F/ 0.1 ppm(v)
Trend Chart	: for Last 100 min. (30 sec./point)
Sample flow	: 1-5 L/min.
Temperature	: 0/+45 °C
Operation pressure	: 1 Atmosphere
Max. Pressure	: 40 MPa
Sample Connection	: S.S. 1/8" S-LOCK Fittings
Power	: Built in Rechargeable Li-ion Battery for 12 Hrs
Charger Power	: 100-240 VAC, 50/ 60 Hz
Output	: RS232 & USB (10 sec./point).
Weight	: Approx. 5Kg
Option	: SD Card

Made in Taiwan



Toplab Instruments Co., Ltd.

5F., No. 5, Alley 1, Lane 214, Sec. 4, Chengong Rd., Neihu, Taipei, Taiwan.

Tel : 886-2-87912436 Fax : 886-2-87912416