



Portable Microprocessor Dewpoint meter




Features :

- 4.3" Touch control screen
- Operation Easily, Large Words
- Dew Point/ ppm(v) Switchable
- Realtime Trend Chart
- Compact Design and Weight Balance
- Built in Rechargeable Battery for 12 Hours
- Wide Measuring Range
- NPL Traceable Calibration
- Readable CSV Format Data by USB Disk

Specifications:

TouchDew TD-301P	
Range	+20 to -100°C, or 0 to 3000 ppmv
Accuracy	± 2 °C
Display	4.3" Touch screen
Display Unit	°C/ °F Dewpoint , ppmv
Resolution	0.1°C/ 0.01°F/ 0.1ppmv
Trend Diagram	100 minutes (30 sec/pt.)
Output	Rs232 & USB (10 sec/pt.)
Operation	
Sample Flow	1-5L/min.
Temperature	0 to +45 °C
Pressure	1 Atmosphere
Max. Pressure	6 BarG
Connection	S.S. 1/4" S-LOCK Fittings
Power	
Battery	Built in Rechargeable Li-ion Battery for 12 Hrs
Charger	100-240 VAC, 50/ 60 Hz
Dimensions	282 X 315 X 164 mm (Main Body)
Weight	Approx. 5 Kg



Toplab
Instruments

www.toplab17.com

5F., No. 5, Alley 1, Lane 214, Sec. 4, Chengkung Rd., Neihu, Taipei, Taiwan.

Tel : 886-2-87912436 Fax : 886-2-87912416

